

Lithium Manganese Dioxide Battery

Li-MnO₂



Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Maximum Continuous Current(mA)	Maximum Pulse Current(mA)	Operating Temperature(°C)	Maximum Dimensions (mm)	Weight (g)
备注: *CR123A为半密封结构							
CYLINDRICAL CELLS							
CR14250	3.0	650	500	1500	-40°C~+85°C	14.5 X 25.0	11
CR14335	3.0	800	1000	2000	-40°C~+85°C	14.5 X 33.5	14
CR14505	3.0	1600	1500	3000	-40°C~+85°C	14.5 X 50.5	21
CR2	3.0	850	1000	2000	-40°C~+85°C	15.6 X 27.0	13
CR15270	3.0	850	1000	2000	-40°C~+85°C	15.6 X 27.0	13
CR17250	3.0	750	1000	2000	-40°C~+85°C	17.0 X 25.0	14
CR17335	3.0	1500	700	2500	-40°C~+85°C	17.0 X 33.8	16.5
CR123A*	3.0	1500	1500	3000	-40°C~+70°C	17.0 X 34.5	17
CR17450	3.0	2400	1500	3000	-40°C~+85°C	17.0 X 45.0	23
CR17505	3.0	2400	1500	3000	-40°C~+85°C	17.0 X 50.5	30
CR18505	3.0	2800	2000	3000	-40°C~+85°C	18.5 X 50.5	35
CR26500	3.0	5000	2000	3000	-40°C~+85°C	26.0 X 50.5	62
CR34615	3.0	10000	2000	3000	-40°C~+85°C	34.0 X 61.5	125
2CR5	6.0	1500	1500	3000	-40°C~+85°C	34.0 X 17.0 X 45.0	42
CR-P2	6.0	1500	1500	3000	-40°C~+85°C	35.0 X 19.5 X 36.0	42
CR14250SE	3.0	950	7	70	-40°C~+85°C	14.5 X 25.0	11.5
CR17335SE	3.0	2000	10	100	-40°C~+85°C	17.0 X 33.55	18
BUTTON CELLS							
CR1025	3.0	30	2	5	-20°C~+70°C	10.0 X 2.5	0.6
CR1216	3.0	28	2	5	-20°C~+70°C	12.5 X 1.6	0.7
CR1220	3.0	35	2	5	-20°C~+70°C	12.5 X 2.0	0.9
CR1225	3.0	50	2	5	-20°C~+70°C	12.5 X 2.5	1.0
CR1616	3.0	50	3	8	-20°C~+70°C	16.0 X 1.6	1.2
CR1620	3.0	70	3	8	-20°C~+70°C	16.0 X 2.0	1.3
CR1625	3.0	95	3	8	-20°C~+70°C	16.0 X 2.5	1.4
CR1632	3.0	120	3	8	-20°C~+70°C	16.0 X 3.2	1.6
CR2016	3.0	80	3	15	-20°C~+70°C	20.0 X 1.6	1.8
CR2025	3.0	160	3	15	-20°C~+70°C	20.0 X 2.5	2.5
CR2032	3.0	225	3	15	-20°C~+70°C	20.0 X 3.2	3.1
CR2320	3.0	150	6	25	-20°C~+70°C	23.0 X 2.0	2.9
CR2330	3.0	225	6	25	-20°C~+70°C	23.0 X 3.0	4.0
CR2354	3.0	500	6	25	-20°C~+70°C	23.0 X 5.4	6.0
CR2430	3.0	280	6	25	-20°C~+70°C	24.5 X 3.0	4.5
CR2450	3.0	600	6	25	-20°C~+70°C	24.5 X 5.0	6.5
CR2477	3.0	1000	6	25	-20°C~+70°C	24.5 X 7.7	8.0
CR3032	3.0	500	6	25	-20°C~+70°C	30.0 X 3.2	7.5
BUTTON CELLS FOR LED							
CR2032SL	3.0	300000(CYCLE)	15mA 1.8S ONE CYCLE	15	-20°C~+70°C	20.0 X 3.2	3.1
9 VOLT CELLS							
CR9V-P	9.0	1200	120	400	-40°C~+85°C	26.2 X 17.2 X 49.2	50.5
SOFT PACK CELLS							
CF502445	3.0	1100	120	400	-40°C~+60°C	5.2 X 25.0 X 45.0	9
CF284646	3.0	800			-40°C~+60°C	2.9 X 46.0 X 46.0	9
CF652230	3.0	800	300	500	-40°C~+60°C	6.7 X 23.0 X 31.0	6.5

※Latest version can be downloaded from EVE website at www.evebattery.com

